

Industrial Grade LCD Touch Monitor



Hopitality / Fast Food / Table Service



Transportation / Airline Counters



Financial / Banking



Medical



- Rugged and Solid Base Design
- Great Cable Management
- Spill Resistant Commercial Grade Housing
- 15" TFT Active Matrix LCD
- Standard Integrated Triple Track MCR
- Optional Integrated Triple Track MCR *with* Fingerprint Reader
- On Screen Display
- Hidden Power Switch and Control Panel
- 5-Wire Resistive Touch
- USB Touch Screen Interface
- VGA Video Interface
- Easily Wall Mountable



SPM-T15 LCD Touch Screen Monitor



Integrated Triple Track Card Reader Standard



Hidden Liquid Resistant Control Panel



Discreet, Yet Easy to Access Ports



SPM-T15 Monitor, MCR, Power Supply and Cord, VGA Cable, USB Cable, Installation Guide and Blank Name Plate Cover

Options and Upgrades

Configure your system with these easy to add options:

- Encrypting Triple Track Card Reader
- Integrated Triple Track MCR with Fingerprint Reader
- Wall Mount Brackets with Standard VESA Configuration

Applications

The flexible SPM-T15 can be combined with a PC to create a distributed workstation for use in applications like these:

- Airline Counters
- Auto Parts
- Automotive Services
- Book Stores
- Convenience Stores
- Digital Signs
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- License Issue
- Medical
- Message Stations
- Municipalities
- Point of Sale
- Quick Service Restaurant
- Rental Car Counters
- Retail Scanning
- Self Service
- Streaming Video
- Table Service Restaurant
- Training
- Touch Kitchen Video
- Unattended Workstations

Specifications

Display LCD:	15" TFT Active Matrix LCD
Resolution:	1024 x 768
Brightness:	250 cd/m ²
Touch Panel:	5-Wire Resistive Touch
MCR:	Integrated USB Interface Triple Track MCR
Colors:	16.2 Million
Contrast Ratio:	500:1
Adjustable Angle:	0° to 90°
Viewing Angle:	H = 150° V = 130° (Left:75° / Right:75° / Up:70° / Down: 60°)
Input Signal:	Analog RGB
Serial Port:	Not Applicable
USB Port – External:	Touchscreen (Penmount 6000 Controller : C8051F321) /
Internal:	MCR
Keyboard Port:	Not Applicable
VGA Port:	One D-Sub 15-Pin
DVI Port:	Not Applicable
Operating Temperature:	32° to 104°F (0° to 40°C)
Humidity:	10% to 90% (Non-Condensing)
Wall / Ceiling Mount:	VESA Holes 75 x 75mm
Power Supply:	DC 12V (3.33A) External Power Adapter
Current/Power Usage:	0.25A / < 30W
Overall Dimensions:	13-7/8"W x 12"H x 8-5/8"D
Carton Dimensions:	18-1/2"W x 11"H x 15-7/8"D
Product Weight:	9.73 lbs.
Shipping Weight:	15.2 lbs.
Safety and EMI:	CE, FCC, RoHS

The monitor's sturdy base is reinforced with aluminum, adding weight for strength, stability, and reliability. Optional VESA wall mount brackets are designed for multiple mounting options.



SPM-T15's Sturdy Base



Other VESA Wall and Ceiling Mount Brackets Available

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features/specifications are subject to change without notice.

© 2014, Printed in U.S.A.

Lit-175a

SAM4S